

and providing to said computer X-ray data corresponding to the intensity of transmitted radiation,

over the area of the thus-exposed ensemble, calculating [a value] values characteristic of said target object of said specific material of interest in said ensemble of objects, and therewith identifying said target object,

systematically utilizing in said calculations X-ray transmission data of rays from said stationary X-ray exposure system passing through said ensemble of objects, including rays passing through said target object of said specific material of interest as well as rays passing near but not through said target object to remove the contribution of overlying and underlying material from the calculated value characteristic of said target object of said specific material of interest, and

automatically indicating the presence of said target object while said ensemble of objects progresses on said conveyor.

83. The method of claim 82 wherein X-ray data from rays that pass through different regions of said target object of said specific material of interest are employed in said calculations in a manner that effectively averages many pixels over contiguous areas to reduce noise in calculating said values.

115. (Amended) A device for detecting a target object of a specific material of interest in [an] a continuously moving ensemble of initially unidentified objects, comprising [for use with] a conveyor arranged to move said ensemble of objects continuously through an inspection station [comprising:].

a stationary X-ray exposure system [,] and a stationary X-ray detection system both constructed to operate cooperatively with said conveyor, and a computer operatively connected to said detection system,

said stationary X-ray exposure system constructed and positioned to progressively expose, at said inspection station, said ensemble of initially unidentified objects to X-ray radiation by continuous movement of said ensemble through a beam produced by said X-ray-exposure system,

said stationary X-ray detection system positioned to detect X-ray radiation transmitted through said ensemble of objects, and constructed to provide to said computer X-ray data corresponding to the intensity of transmitted radiation,

said computer programmed to calculate, over the area of the thus-exposed ensemble, values [a value] characteristic of said target object of said specific material of interest in said ensemble of objects, and therewith identifying said target object,

said computer programmed to systematically utilize in said calculations X-ray transmission data of rays from said stationary X-ray exposure system passing through said ensemble of objects, including rays passing through said target object of said specific material of interest as well as rays passing near but not through said target object to remove the contribution of overlying and underlying material from the calculated value characteristic of said target object of said specific material, and

said computer programmed to indicate the presence of said target object.

Please cancel dependent claim 87 and rewrite in independent form as claim 152.

152. A method of detecting a target object of a specific material of interest in a continuously moving article of luggage or package the contents of which are initially unidentified, comprising:

providing a stationary X-ray exposure system capable of producing at least one fan beam of X-ray radiation, a stationary X-ray detection system capable of detecting fan beam radiation, and a computer operatively connected to said detection system,

continuously moving said ensemble of objects on a conveyor through an inspection station,

at said inspection station, progressively exposing said article of luggage or package to X-ray radiation by continuous movement of said article of luggage or package through said fan beam produced by said stationary X-ray exposure system,

detecting the X-ray radiation transmitted through said article of luggage or package with said stationary X-ray detection system, and providing to said computer X-ray data corresponding to the intensity of transmitted radiation,

over the area of the thus-exposed article of luggage or package, calculating values characteristic of said target object of said specific material of interest in said luggage or package and therewith identifying said target object,

systematically utilizing in said calculations X-ray transmission data of rays from said stationary X-ray exposure system passing through said article of luggage or package,